

<b>Source Classification Code Table</b>						
<b>SCC Code</b>	<b>Description 1</b>	<b>Description 2</b>	<b>Description 3</b>	<b>Description 4 (<i>corresponds to OEPA description</i>)</b>		
40202202	Petroleum and Solvent Evaporation	Surface Coating Operations	Plastic Parts	Coating Cleaning/ Pretreatment		
40202203				Coating Mixing		
40202204				Coating Storage		
40202205				Coating Equipment Cleanup		
40202280				Maskant Application		
<b>Best Available Technology Limit Table</b>						
<b>BAT #</b>	<b><u>OEPA Description</u></b>	<b>Pollutant</b>	<b>Control equip/ Control meas.</b>	<b>Eff.</b>	<b>Stack</b>	<b>Fugitive</b>
00001	<ul style="list-style-type: none"> <li>● Coating Cleaning/ Pretreatment; or</li> <li>● Coating Equipment Cleanup</li> </ul>	VOC	Work Practices	N/A		Work Practice
00002	<ul style="list-style-type: none"> <li>● Coating Mixing; or</li> <li>● Coating Storage</li> </ul>	VOC	Work Practices	N/A		Work Practice
00003	Maskant Application	VOC	<p>If MASK Coatings are less than 0.5 mm thick (dry) and coated area is less than 25 sq inch then Work Practices and Application Methods in this section</p> <p>If MASK is greater than above Mask must follow Coating Operation Control Options</p>	N/A		Work Practice unless Maskant usage greater than 0.5 mm thick and 25 sq inches, where Maskant usage must follow coating content limits.
<b>BAT Operational Restrictions, Monitoring, Record Keeping, Reporting and Testing Table</b>						

<b>BAT #</b>	<b>Operational Restriction</b>	<b>Monitoring and Record Keeping</b>	<b>Reporting</b>	<b>Testing</b>
00001	(a) Store all VOC-containing material and used shop towels in closed containers (b) containers kept closed (c) minimize spills (d) convey all coatings, thinners etc in closed containers or pipes (e) equipment cleaning done without atomizing solvent, and all spent solvent is captured in closed containers.	-	-	-
00002	(a) Store all VOC-containing material in closed containers (b) containers kept closed (c) minimize spills (d) convey all coatings, thinners etc in closed containers or pipes	-	-	-
00003	(a)Store all VOC-containing material and used shop towels in closed containers (b) containers kept closed (c) minimize spills (d) convey all coatings, thinners etc in closed containers or pipes (e) equipment cleaning done without atomizing solvent, and all spent solvent is captured in closed containers.  APPLICATION METHODS electrostatic application, HVLP spray, flow coat, roller coat, dip coat, airless spray, air-assisted airless spray, or equivalent to HVLP	Monitor thickness and area of Maskant to ensure compliance is met.	-	-