

3745-69-44

**Inspections of drip pads.**

- (A) During construction or installation, liners and cover systems (e.g., membranes, sheets, or coatings) ~~shall~~must be inspected for uniformity, damage, and imperfections (e.g., holes, cracks, thin spots, or foreign materials). Immediately after construction or installation, liners ~~shall~~must be inspected and certified as meeting the requirements of rule 3745-69-43 of the Administrative Code by ~~an independent~~a qualified, ~~registered~~ professional engineer. ~~The~~This certification ~~shall~~must be maintained at the facility as part of the facility operating record. After installation, liners and covers ~~shall~~must be inspected to ensure tight seams and joints and the absence of tears, punctures, or blisters.
- (B) While a drip pad is in operation, it ~~shall~~must be inspected weekly and after storms to detect evidence of any of the following:
- (1) Deterioration, malfunctions or improper operation of run-on and run-off control systems;
  - (2) The presence of leakage in and proper functioning of leakage detection system.
  - (3) Deterioration or cracking of the drip pad surface.

~~[Note: See paragraph (M) of rule 3745-69-43 of the Administrative Code for remedial action required if deterioration or leakage is detected.]~~

[Comment: See paragraph (M) of rule 3745-69-43 of the Administrative Code for remedial action required if deterioration or leakage is detected.]

Effective: 09/05/2010

R.C. 119.032 review dates: Exempt

CERTIFIED ELECTRONICALLY

---

Certification

07/23/2010

---

Date

Promulgated Under: 119.03  
Statutory Authority: 3734.12  
Rule Amplifies: 3734.12  
Prior Effective Dates: 09/02/1997